

PFA ROD

DIA (mm)	Tolerance Standard (mm)	Natural PFA Rod (kg)		
3	+ 0.2	0.008		
5	+ 0.4	0.021		
6	+ 0.2	0.030		
8	+ 0.4	0.054		
10	+ 0.2	0.084		
12	+ 0.6	0.122		
15	+ 0.6	0.190		
20	+ 0.2	0.338		
25	+ 1.0	0.528		
30	+ 1.0	0.760		
35	+ 0.2	1.034		
40	+ 1.5	1.351		
45	+ 1.5	1.710		
50	+ 0.2	2.111		
55	+ 0.3	2.554		
60	+ 2.0	3.039		
65	+ 0.3	3.567		
70	+ 2.0	4.137		
75	+ 2.0	4.749		
80	+ 0.3	5.404		
85	+ 2.0	6.100		
90	+ 0.3	6.839		
95	+ 0.4	7.620		
100	+ 3.5	8.443		
110	+ 0.4	10.216		
120	+ 3.5	12.158		
130	+ 0.4	14.269		

Remark:

1. Tolerance is according to DIN Length: + 0~3 %, width: + 0~ 3%.
2. it is theoretical value for above spec, with the Length 500mm
3. Taking objective as standard, listed data are for reference only.
4. The products above have been strictly treated with tempering; the strain value has met the minimum.