

POM ROD

DIA (mm)	Tolerance Standard (mm)	POM ROD (kg)	Anti Static POM ROD(kg)	Conductivity/ MOS2 POM ROD (kg)
3	+ 0.2	0.010	0.010	0.010
5	+ 0.4	0.028	0.028	0.029
6	+ 0.2	0.040	0.040	0.041
8	+ 0.4	0.072	0.071	0.073
10	+ 0.2	0.112	0.112	0.115
12	+ 0.6	0.162	0.161	0.165
15	+ 0.6	0.253	0.251	0.258
20	+ 0.2	0.449	0.446	0.459
25	+ 1.0	0.702	0.697	0.717
30	+ 1.0	1.011	1.004	1.032
35	+ 0.2	1.376	1.366	1.405
40	+ 1.5	1.797	1.784	1.835
45	+ 1.5	2.274	2.258	2.322
50	+ 1.5	2.808	2.788	2.867
55	+ 0.3	3.397	3.374	3.469
60	+ 2.0	4.043	4.015	4.128
65	+ 0.3	4.745	4.712	4.845
70	+ 2.0	5.503	5.465	5.619
75	+ 2.0	6.318	6.273	6.450
80	+ 0.3	7.188	7.138	7.339
85	+ 2.0	8.115	8.058	8.285
90	+ 0.3	9.097	9.034	9.288
95	+ 0.4	10.136	10.065	10.349
100	+ 3.5	11.231	11.153	11.467
110	+ 3.5	13.590	13.495	13.875
120	+ 3.5	16.173	16.060	16.512
130	+ 3.5	18.981	18.848	19.379
140	+ 0.5	22.013	21.859	22.475
150	+ 4.5	25.270	25.093	25.800
160	+ 0.5	28.752	28.551	29.355
180	+ 4.5	36.389	36.135	37.152
200	+ 4.5	44.925	44.611	45.867
220	+ 4.5	54.359	53.979	55.499
250	+ 4.5	70.195	69.704	71.668

Remark:

1. Tolerance is according to DIN Length: + 0~3 %, width: + 0~ 3%.
2. it is theoretical value for above spec, with the Length 1000mm
3. Taking objective as standard, listed data are for reference only.
4. The products above have been strictly treated with tempering; the strain value has met the minimum.

