

HDPE ROD

DIA (mm)	Tolerance Standard (mm)	HDPE (kg)	HDPE Anti Static (kg)	HDPE Conductivity (kg)
3	+ 0.2	0.007	0.007	0.007
5	+ 0.4	0.019	0.019	0.020
6	+ 0.2	0.027	0.027	0.029
8	+ 0.4	0.048	0.048	0.051
10		0.075	0.075	0.079
12	+ 0.2	0.109	0.107	0.114
15	+ 0.6	0.170	0.168	0.178
20		0.302	0.298	0.317
25	+ 0.2	0.471	0.466	0.496
30	+ 1.0	0.679	0.672	0.714
35		0.924	0.914	0.972
40	+ 0.2	1.206	1.194	1.269
45	+ 1.5	1.527	1.511	1.606
50		1.885	1.865	1.983
55		2.281	2.257	2.400
60		2.714	2.686	2.856
65		3.186	3.152	3.351
70	+ 0.3	3.695	3.656	3.887
75	+ 2.0	4.241	4.197	4.462
80		4.825	4.775	5.077
85		5.448	5.391	5.731
90		6.107	6.044	6.425
95		6.805	6.734	7.159
100		7.540	7.461	7.933
110	+ 0.4	9.123	9.028	9.598
120	+ 3.5	10.857	10.744	11.423
130		12.742	12.610	13.406
140		14.778	14.624	15.548
150		16.965	16.788	17.848
160		19.302	19.101	20.307
180	+ 0.5	24.429	24.175	25.701
200	+ 4.5	30.159	29.845	31.730
220		36.493	36.113	38.393
240		43.429	42.977	45.691
260		50.969	50.438	53.624
300		67.858	67.151	71.393

Remark:

1. Tolerance is according to DIN Length: + 0~3 %, width: + 0~ 3%.
2. it is theoretical value for above spec, with the Length 1000mm
3. Taking objective as standard, listed data are for reference only.
4. The products above have been strictly treated with tempering; the strain value has met the minimum.